

Department	Case code	Case description
Bakery	B0124/04/06/08/12 - 1250	Cake drawer basic - 1250 High

Physical Properties:

Available Case Lengths	Total Display Area (TDA) [m ²]	Volume [m ³]	Allowable Load [kg]	Net Weight [kg]
4'	0.9827	0.225	XX.X	XX.X
6'	1.4741	0.337	XX.X	XX.X
8'	1.9654	0.449	XX.X	XX.X
12'	2.9481	0.674	XX.X	XX.X

Electrical:

Available Case Lengths	Fans		Heaters	
	Shaded Pole [W]	ECM* [W]	Anti-sweat [W]	Defrost** [W]
4'	2 x 32W	2 x 24W	1 x 7W/m x 2.0m	
6'	2 x 32W	2 x 24W	1 x 7W/m x 3.2m	
8'	2 x 32W	2 x 24W	1 x 7W/m x 4.88m	
12'	4 x 32W	4 x 24W	1 x 7W/m x 7.3m	
Glass PE	-	-	-	-

Case Lengths	Lighting (T5 HO Tubes)		Lighting (T8 Tubes)	
	Case [W]	Shelf [W]	Case [W]	Shelf [W]
4'	3 x 4' [162W]		3 x 3' [90W]	
6'	6 x 3' [234W]		3 x 5' [174W]	
8'	6 x 4' [324W]		3 x 3' & 3 x 4' [198W]	
12'	9 x 4' [486W]		3 x 3' & 6 x 4' [306W]	

* High efficiency option.

** Not used when using high efficiency set up.

Note: All specifications for high efficiency units are based on the use of a full high efficiency setup including high efficiency coils, electronic expansion valves and ECM fans.

Refrigeration Requirements:

	Refrigeration [W/ft]	Evaporation Temp. [°C]
Standard	90	-5
High Efficiency		