

Department	Case code	Case description
Bakery	B0141/04/06/08/12 - 1250	Cake SQ gls drawer - 1250 High

Physical Properties:

Available Case Lengths	Total Display Area (TDA) [m ²]	Volume [m ³]	Allowable Load [kg]	Net Weight [kg]
4'	0.7532	0.183	XX.X	XX.X
6'	1.1298	0.274	XX.X	XX.X
8'	1.5065	0.365	XX.X	XX.X
12'	2.2597	0.548	XX.X	XX.X

Electrical:

Available Case Lengths	Fans		Heaters	
	Shaded Pole [W]	ECM* [W]	Anti-sweat [W]	Defrost** [W]
4'	2 x 32W	2 x 24W	1 x 7W/m x 2.0m	
6'	2 x 32W	2 x 24W	1 x 7W/m x 3.2m	
8'	2 x 32W	2 x 24W	1 x 7W/m x 4.88m	
12'	4 x 32W	4 x 24W	1 x 7W/m x 7.3m	
Glass PE	-	-	-	-

Case Lengths	Lighting (T5 HO Tubes)		Lighting (T8 Tubes)	
	Case [W]	Shelf [W]	Case [W]	Shelf [W]
4'	2 x 4' [108W]		2 x 3' [60W]	
6'	4 x 3' [156W]		2 x 5' [116W]	
8'	4 x 4' [216W]		2 x 3' & 2 x 4' [132W]	
12'	6 x 4' [324W]		2 x 3' & 4 x 4' [204W]	

* High efficiency option.

** Not used when using high efficiency set up.

Note: All specifications for high efficiency units are based on the use of a full high efficiency setup including high efficiency coils, electronic expansion valves and ECM fans.

Refrigeration Requirements:

	Refrigeration [W/ft]	Evaporation Temp. [°C]
Standard	80	-3
High Efficiency		