

Department	Case code	Case description
Dome	B0925/04/06/08/12 - 1350	Combi slope gls cold top, cold bottom

Physical Properties:

Available Case Lengths	Total Display Area (TDA) [m ²]	Volume [m ³]	Allowable Load [kg]	Net Weight [kg]
4'	1.4776	0.282	XX.X	XX.X
6'	2.2213	0.422	XX.X	XX.X
8'	2.965	0.563	XX.X	XX.X
12'	4.4525	0.845	XX.X	XX.X

Electrical:

Available Case Lengths	Fans		Heaters	
	ebm W2E142 [W]	ebm 4650N [W]	Anti-sweat [W]	Defrost* [W]
4'	1 x 27W	-	-	
6'	-	4 x 19W	-	
8'	3 x 27W	-	-	
12'	4 x 27W	-	-	
Glass PE	-	-	-	-

Case Lengths	Lighting (T5 HO Tubes)		Lighting (T8 Tubes)		Lighting (LED Lights)**	
	Case [W]	Shelf [W]	Case [W]	Shelf [W]	Case [W]	Shelf [W]
4'	2 x 4' [108W]	1 x 4' [54W]	2 x 3' [60W]	1 x 3' [30W]		
6'	4 x 3' [156W]	1 x 5' [80W]	2 x 5' [116W]	1 x 5' [58W]		
8'	4 x 4' [216W]	2 x 4' [108W]	2 x 3' & 2 x 4' [132W]	1 x 3' & 1 x 4' [66W]		
12'	6 x 4' [324W]	3 x 4' [162W]	2 x 3' & 4 x 4' [204W]	1 x 3' & 2 x 4' [102W]		

** Available and fitted at customer requirement.

Refrigeration Requirements:

	Refrigeration [W/ft]	Evaporation Temp. [°C]
Standard	375	-6
High Efficiency		