

Department	Case code	Case description
Deli	B1031/04/06/08/12 - 1250	Deli std with big D - 1250 High x 08

### Physical Properties:

Available Case Lengths	Total Display Area (TDA) [m <sup>2</sup> ]	Volume [m <sup>3</sup> ]	Allowable Load [kg]	Net Weight [kg]
4'	0.5248	0.173	XX.X	XX.X
6'	0.7873	0.26	XX.X	XX.X
8'	1.0497	0.346	XX.X	XX.X
12'	1.5745	0.519	XX.X	XX.X

### Electrical:

Available Case Lengths	Fans		Heaters	
	Shaded Pole [W]	ECM* [W]	Anti-sweat [W]	Defrost** [W]
4'	1 x 32W	1 x 24W	2 x 7W/m x 2.0m	1 x 800W
6'	2 x 32W	2 x 24W	2 x 7W/m x 3.2m	1 x 1300W
8'	2 x 32W	2 x 24W	2 x 7W/m x 4.88m	1 x 1600W
12'	3 x 32W	3 x 24W	2 x 7W/m x 7.3m	1 x 2400W
Glass PE	-	-	-	-

Case Lengths	Lighting (T5 HO Tubes)		Lighting (T8 Tubes)	
	Case [W]	Shelf [W]	Case [W]	Shelf [W]
4'	1 x 4' [54W]		1 x 3' [30W]	
6'	2 x 3' [78W]		1 x 5' [58W]	
8'	2 x 4' [108W]		1 x 3' & 1 x 4' [66W]	
12'	3 x 4' [162W]		1 x 3' & 2 x 4' [102W]	

\* High efficiency option.

\*\* Not used when using high efficiency set up.

**Note:** All specifications for high efficiency units are based on the use of a full high efficiency setup including high efficiency coils, electronic expansion valves and ECM fans.

### Refrigeration Requirements:

	Refrigeration [W/ft]	Evaporation Temp. [°C]
Standard	110	-8
High Efficiency		