

Department	Case code	Case description
Deli	B1255/04/06/08/12 - 1250	HiLo s/serve "550" Frt - 1250 High

### Physical Properties:

Available Case Lengths	Total Display Area (TDA) [m <sup>2</sup> ]	Volume [m <sup>3</sup> ]	Allowable Load [kg]	Net Weight [kg]
4'	2.515	0.429	XX.X	XX.X
6'	3.821	0.644	XX.X	XX.X
8'	5.127	0.858	XX.X	XX.X
12'	7.7391	1.287	XX.X	XX.X

### Electrical:

Available Case Lengths	Fans		Heaters	
	Shaded Pole [W]	ECM* [W]	Anti-sweat [W]	Defrost** [W]
4'	2 x 38W	2 x 24W	-	1 x 800W
6'	3 x 38W	3 x 24W	-	1 x 1200W
8'	4 x 38W	4 x 24W	-	1 x 1600W
12'	6 x 38W	6 x 24W	-	1 x 2400W
Glass PE	-	-	-	-

Case Lengths	Lighting (T5 HO Tubes)		Lighting (T8 Tubes)	
	Case [W]	Shelf [W]	Case [W]	Shelf [W]
4'	1 x 4' [54W]	(T8 Tubes)	1 x 3' [30W]	2 x 3' [60W]
6'	2 x 3' [78W]	(T8 Tubes)	1 x 5' [58W]	2 x 5' [116W]
8'	2 x 4' [108W]	(T8 Tubes)	1 x 3' & 1 x 4' [66W]	4 x 3' [120W]
12'	3 x 4' [162W]	(T8 Tubes)	1 x 3' & 2 x 4' [102W]	6 x 3' [160W]

\* High efficiency option.

\*\* Not used when using high efficiency set up.

**Note:** All specifications for high efficiency units are based on the use of a full high efficiency setup including high efficiency coils, lighting, electronic expansion valves and ECM fans.

### Refrigeration Requirements:

	Refrigeration [W/ft]	Evaporation Temp. [°C]
Standard	425	-7
High Efficiency		