

Department	Case code	Case description
Upright	B2070/04/06/07/08/12	Dairy Spec basic - 1530 High

Physical Properties:

Available Case Lengths	Total Display Area (TDA) [m ²]	Volume [m ³]	Allowable Load [kg]	Net Weight [kg]
4'	1.5006	0.72	XX.X	XX.X
6'	2.2509	1.079	XX.X	XX.X
7'	1.7547	0.884	XX.X	XX.X
8'	3.0012	1.439	XX.X	XX.X
12'	4.5018	2.159	XX.X	XX.X

Electrical:

Available Case Lengths	Fans		Heaters	
	Shaded Pole [W]	ECM* [W]	Anti-sweat [W]	Defrost** [W]
4'	2 x 38W	2 x 14W	1 x 7W/m x 2.0m	1 x 800W
6'	3 x 38W	3 x 14W	1 x 7W/m x 3.2m	1 x 1200W
7'	3 x 38W	3 x 14W	1 x 7W/m x 2.0m	1 x 1300W
8'	4 x 38W	4 x 14W	1 x 7W/m x 4.88m	1 x 1600W
12'	6 x 38W	6 x 14W	1 x 7W/m x 7.3m	1 x 2400W
Glass E	-	-	1 x 7W/m x 7.3m	-

Case Lengths	Lighting (T5 HO Tubes)		Lighting (T8 Tubes)	
	Case [W]	Shelf [W]	Case [W]	Shelf [W]
4'	1 x 4' [54W]	(T8 Tubes)	1 x 3' [30W]	3 x 3' [90W]
6'	2 x 3' [78W]	(T8 Tubes)	1x 5' [58W]	3 x 5' [174W]
7'	1 x 3' [39W]	(T8 Tubes)	1x 3' [30W]	2 x 2' & 1 x 5' [94W]
8'	2 x 4' [108W]	(T8 Tubes)	1 x 3' & 1 x 4' [66W]	6 x 3' [180W]
12'	3 x 4' [162W]	(T8 Tubes)	1 x 3' & 2 x 4' [102W]	9 x 3' [270W]

* High efficiency option.

** Not used when using high efficiency set up.

Note: All specifications for high efficiency units are based on the use of a full high efficiency setup including high efficiency coils, electronic expansion valves and ECM fans.

Refrigeration Requirements:

	Refrigeration [W/ft]	Evaporation Temp. [°C]
Standard	440	-10
High Efficiency		