

Department	Case code	Case description
Upright	B2701/04/06/08/12	Live wall Lofty

Physical Properties:

Available Case Lengths	Total Display Area (TDA) [m ²]	Volume [m ³]	Allowable Load [kg]	Net Weight [kg]
4'	1.902	0.667	XX.X	XX.X
6'	2.853	1.001	XX.X	XX.X
8'	3.804	1.335	XX.X	XX.X
12'	5.7059	2.002	XX.X	XX.X

Electrical:

Available Case Lengths	Fans		Heaters	
	Shaded Pole [W]	ECM* [W]	Anti-sweat [W]	Defrost** [W]
4'	2 x 38W	2 x 25W		1 x 800W
6'	3 x 38W	3 x 25W		1 x 1200W
8'	4 x 38W	4 x 25W		1 x 1600W
12'	6 x 38W	6 x 25W		1 x 2400W
Glass PE	-	-	1 x 16W/m x 3.5m	-

Case Lengths	Lighting (T5 HO Tubes)		Lighting (T8 Tubes)	
	Case [W]	Shelf [W]	Case [W]	Shelf [W]
4'	1 x 4' [54W]	(T8 Tubes)	1 x 3' [30W]	5 x 3' [150W]
6'	2 x 3' [78W]	(T8 Tubes)	1 x 5' [58W]	5 x 5' [290W]
8'	2 x 4' [108W]	(T8 Tubes)	1 x 3' & 1 x 4' [66W]	10 x 3' [300W]
12'	3 x 4' [162W]	(T8 Tubes)	1 x 3' & 2 x 4' [102W]	15 x 3' [450W]

* High efficiency option.

** Not used when using high efficiency set up.

Note: All specifications for high efficiency units are based on the use of a full high efficiency setup including high efficiency coils, electronic expansion valves and ECM fans.

Refrigeration Requirements:

	Refrigeration [W/ft]	Evaporation Temp. [°C]
Standard	520	-8
High Efficiency		