

| Department | Case code | Case description |
|------------|-------------|------------------------------|
| Self Cont | B7580/04/06 | SANDWICH W.W. Self contained |

Physical Properties:

| Available Case Lengths | Total Display Area (TDA) [m ²] | Volume [m ³] | Allowable Load [kg] | Net Weight [kg] |
|------------------------|--|--------------------------|---------------------|-----------------|
| 4' | 1.2127 | 0.351 | XX.X | XX.X |
| 6' | 1.819 | 0.526 | XX.X | XX.X |

Electrical:

| Available Case Lengths | Fans | | Compressor | Heaters | Solenoid Valve [W] |
|------------------------|-------------------|-------------------|-------------------------|------------------|--------------------|
| | ebm [W] | Condenser Fan [W] | CAJ4517E & CAJ4519T [W] | Tray Element [W] | |
| 4' | W2E142 2 x 27W | 2 x 90W | CAJ4517E 1395W | 1 x 1000W | 1 x 10W |
| 6' | 4650N 4 x 19W | 2 x 90W | CAJ4519T 1938W | 1 x 1000W | 1 x 10W |

| Case Lengths | Lighting (T5 HO Tubes) | | Lighting (LED Lights)* | |
|--------------|------------------------|-----------|------------------------|-----------|
| | Case [W] | Shelf [W] | Case [W] | Shelf [W] |
| 4' | 1 x 4' [54W] | | | |
| 6' | 2 x 3' [78W] | | | |

* Available and fitted at customer requirement

Refrigeration Requirements:

| | Refrigeration [W/ft] | Evaporation Temp. [°C] |
|-----------------|----------------------|------------------------|
| Standard | - | - |
| High Efficiency | | |