

Department	Case code	Case description
Butchery	B9501/04/06/08/12	High meat Lofty

### Physical Properties:

Available Case Lengths	Total Display Area (TDA) [m <sup>2</sup> ]	Volume [m <sup>3</sup> ]	Allowable Load [kg]	Net Weight [kg]
4'	1.9106	1.045	XX.X	XX.X
6'	2.866	1.567	XX.X	XX.X
8'	3.8213	2.089	XX.X	XX.X
12'	5.7332	3.134	XX.X	XX.X

### Electrical:

Available Case Lengths	Fans		Heaters	
	Shaded Pole [W]	ECM* [W]	Anti-sweat [W]	Defrost** [W]
4'	2 x 38W	2 x 25W	1 x 7W/m x 2.0m	1 x 800W
6'	3 x 38W	3 x 25W	1 x 7W/m x 3.2m	1 x 1200W
8'	4 x 38W	4 x 25W	1 x 7W/m x 4.88m	1 x 1600W
12'	6 x 38W	6 x 25W	1 x 7W/m x 7.3m	1 x 2400W
Glass PE	-	-	1 x 16W/m x 3.2m	-

Case Lengths	Lighting (T5 HO Tubes)		Lighting (T8 Tubes)	
	Case [W]	Shelf [W]	Case [W]	Shelf [W]
4'	2 x 4' [108W]	(T8 Tubes)	2 x 3' [60W]	4 x 3' [120W]
6'	4x 3' [156W]	(T8 Tubes)	2 x 5' [116W]	4 x 5' [232W]
8'	4 x 4' [216W]	(T8 Tubes)	2 x 3' & 2 x 4' [132W]	8 x 3' [240W]
12'	6 x 4' [324W]	(T8 Tubes)	2 x 3' & 4 x 4' [204W]	12 x 3' [360W]

\* High efficiency option.

\*\* Not used when using high efficiency set up.

**Note:** All specifications for high efficiency units are based on the use of a full high efficiency setup including high efficiency coils, electronic expansion valves and ECM fans.

### Refrigeration Requirements:

	Refrigeration [W/ft]	Evaporation Temp. [°C]
Standard	527	-8
High Efficiency		